

STAINLESS STEEL CAMLOCK COUPLING

Material:Stainless steel Method: Investment Casting
 Surface Finish : Shotting Handle: Stainless Steel
 Gasket:NBR Safety pin:Stainless Steel
 Thread:ISO228(BSP)/ISO7(BSPT)/ANSI B1.20(NPT) Standard:MIL A-A-59326/EN14420-7(DIN2828)

STYLE
TYPE A



MALE ADAPTER
X
FEMALE THREAD

SIZE	CODE
1/2"(DN15)	A050-304&A050-316
3/4"(DN20)	A075-304&A075-316
1"(DN25)	A100-304&A100-316
1-1/4"(DN32)	A125-304&A125-316
1-1/2"(DN40)	A150-304&A150-316
2"(DN50)	A200-304&A200-316
2-1/2"(DN65)	A250-304&A250-316
3"(DN80)	A300-304&A300-316
4"(DN100)	A400-304&A400-316
5"(DN125)	A500-304&A500-316
6"(DN150)	A600-304&A600-316

STYLE
TYPE E



MALE ADAPTER
X
HOSE SHANK

SIZE	CODE
1/2"(DN15)	E050-304&E050-316
3/4"(DN20)	E075-304&E075-316
1"(DN25)	E100-304&E100-316
1-1/4"(DN32)	E125-304&E125-316
1-1/2"(DN40)	E150-304&E150-316
2"(DN50)	E200-304&E200-316
2-1/2"(DN65)	E250-304&E250-316
3"(DN80)	E300-304&E300-316
4"(DN100)	E400-304&E400-316
5"(DN125)	E500-304&E500-316
6"(DN150)	E600-304&E600-316

STYLE
TYPE B



FEMALE COUPLER
X
MALE THREAD

SIZE	CODE
1/2"(DN15)	B050-304&B050-316
3/4"(DN20)	B075-304&B075-316
1"(DN25)	B100-304&B100-316
1-1/4"(DN32)	B125-304&B125-316
1-1/2"(DN40)	B150-304&B150-316
2"(DN50)	B200-304&B200-316
2-1/2"(DN65)	B250-304&B250-316
3"(DN80)	B300-304&B300-316
4"(DN100)	B400-304&B400-316
5"(DN125)	B500-304&B500-316
6"(DN150)	B600-304&B600-316

STYLE
TYPE F



MALE ADAPTER
X
MALE THREAD

SIZE	CODE
1/2"(DN15)	F050-304&F050-316
3/4"(DN20)	F075-304&F075-316
1"(DN25)	F100-304&F100-316
1-1/4"(DN32)	F125-304&F125-316
1-1/2"(DN40)	F150-304&F150-316
2"(DN50)	F200-304&F200-316
2-1/2"(DN65)	F250-304&F250-316
3"(DN80)	F300-304&F300-316
4"(DN100)	F400-304&F400-316
5"(DN125)	F500-304&F500-316
6"(DN150)	F600-304&F600-316

STYLE
TYPE C



FEMALE COUPLER
X
HOSE SHANK

SIZE	CODE
1/2"(DN15)	C050-304&C050-316
3/4"(DN20)	C075-304&C075-316
1"(DN25)	C100-304&C100-316
1-1/4"(DN32)	C125-304&C125-316
1-1/2"(DN40)	C150-304&C150-316
2"(DN50)	C200-304&C200-316
2-1/2"(DN65)	C250-304&C250-316
3"(DN80)	C300-304&C300-316
4"(DN100)	C400-304&C400-316
5"(DN125)	C500-304&C500-316
6"(DN150)	C600-304&C600-316

STYLE
TYPE DC



DUST CAP

SIZE	CODE
1/2"(DN15)	DC050-304&DC050-316
3/4"(DN20)	DC075-304&DC075-316
1"(DN25)	DC100-304&DC100-316
1-1/4"(DN32)	DC125-304&DC125-316
1-1/2"(DN40)	DC150-304&DC150-316
2"(DN50)	DC200-304&DC200-316
2-1/2"(DN65)	DC250-304&DC250-316
3"(DN80)	DC300-304&DC300-316
4"(DN100)	DC400-304&DC400-316
5"(DN125)	DC500-304&DC500-316
6"(DN150)	DC600-304&DC600-316

STYLE
TYPE D



FEMALE COUPLER
X
FEMALE THREAD

SIZE	CODE
1/2"(DN15)	D050-304&D050-316
3/4"(DN20)	D075-304&D075-316
1"(DN25)	D100-304&D100-316
1-1/4"(DN32)	D125-304&D125-316
1-1/2"(DN40)	D150-304&D150-316
2"(DN50)	D200-304&D200-316
2-1/2"(DN65)	D250-304&D250-316
3"(DN80)	D300-304&D300-316
4"(DN100)	D400-304&D400-316
5"(DN125)	D500-304&D500-316
6"(DN150)	D600-304&D600-316

STYLE
TYPE DP



DUST PLUG

SIZE	CODE
1/2"(DN15)	DP050-304&DP050-316
3/4"(DN20)	DP075-304&DP075-316
1"(DN25)	DP100-304&DP100-316
1-1/4"(DN32)	DP125-304&DP125-316
1-1/2"(DN40)	DP150-304&DP150-316
2"(DN50)	DP200-304&DP200-316
2-1/2"(DN65)	DP250-304&DP250-316
3"(DN80)	DP300-304&DP300-316
4"(DN100)	DP400-304&DP400-316
5"(DN125)	DP500-304&DP500-316
6"(DN150)	DP600-304&DP600-316