



Rolled Beams UPN

Travi UPN
UPN Träger
Poutrelles UPN
Perfil UPN

DIN 1026-1
NF A 45-202
EN 10279

Type		h	b	s	t	kg/m	Product lengths - Herstellungslängen - Lunghezze di fabbricazione - Longueurs de fabrication - Longitudes de fabricación
UPN 80		80	45	6	8	8,65	6m ► 15m (-0/+100 mm)
UPN 100		100	50	6	8,5	10,6	
UPN 120		120	55	7	9	13,3	
UPN 140		140	60	7	10	16,0	
UPN 160		160	65	7,5	10,5	18,8	6m ► 25m (-0/+100 mm)
UPN 180		180	70	8	11	22,0	
UPN 200		200	75	8,5	11,5	25,3	
UPN 220		220	80	9	12,5	29,4	
UPN 240		240	85	9,5	13	33,2	
UPN 260°		260	90	10	14	37,9	
UPN 280°		280	95	10	15	41,8	
UPN 300°		300	100	10	16	46,2	

* on request - a richiesta - auf Anfrage - sur demande - a solicitud

Process tolerances
Tolleranze di fabbricazione
Herstellungstoleranzen
Tolérances de fabrication
Tolerancias de fabricación

h (mm)	65 < h ≤ 200	65 < h ≤ 200		
	± 2,0	± 3,0		
b (mm)	b ≤ 50	50 < b ≤ 100		
	± 1,5	± 2,0		
s (mm)	s ≤ 10			
	± 0,50			
t (mm)	t ≤ 10	10 < t ≤ 15	t > 15	
	-0,5 / + *	-1,0 / + *	-1,5 / + *	

* plus tolerances are limited by the permissible exceeding of weight