

Material: Aluminum Alloy, Stainless Steel  
 Gasket: NBR  
 Thread: ISO228(BSP)/ISO7(BSPT)/ANSI B1.2(NPT)  
 Standard: EN14420-8

**STYLE**



GULLEMIN COUPLING WITH LOCK RING AND MULTI-SERRATED HOSE TAIL

SIZE	CODE
1-1/2"(DN40)	GHL-150M-AL/SS
2"(DN50)	GHL-200M-AL/SS
2-1/2"(DN65)	GHL-250M-AL/SS
3"(DN80)	GHL-300M-AL/SS
4"(DN100)	GHL-400M-AL/SS

**STYLE**



GULLEMIN COUPLING WITH FEMALE BSP THREAD WITHOUT LOCKING RING

SIZE	CODE
1-1/2"(DN40)	GF-150-AL/SS
2"(DN50)	GF-200-AL/SS
2-1/2"(DN65)	GF-250-AL/SS
3"(DN80)	GF-300-AL/SS
4"(DN100)	GF-400-AL/SS

**STYLE**



GULLEMIN COUPLING WITH LOCK RING AND MULTI-SERRATED SHORT HOSE TAIL

SIZE	CODE
1-1/2"(DN40)	GHL-150L-AL/SS
2"(DN50)	GHL-200L-AL/SS
2-1/2"(DN65)	GHL-250L-AL/SS
3"(DN80)	GHL-300L-AL/SS
4"(DN100)	GHL-400L-AL/SS

**STYLE**



GULLEMIN COUPLING WITH LOCK RING AND MALE BSP THREAD

SIZE	CODE
1-1/2"(DN40)	GML-150-AL/SS
2"(DN50)	GML-200-AL/SS
2-1/2"(DN65)	GML-250-AL/SS
3"(DN80)	GML-300-AL/SS
4"(DN100)	GML-400-AL/SS

**STYLE**



GULLEMIN COUPLING WITH LOCK RING AND MULTI-SERRATED LONG HOSE TAIL

SIZE	CODE
1-1/2"(DN40)	GHL-150S-AL/SS
2"(DN50)	GHL-200S-AL/SS
2-1/2"(DN65)	GHL-250S-AL/SS
3"(DN80)	GHL-300S-AL/SS
4"(DN100)	GHL-400S-AL/SS

**STYLE**



GULLEMIN COUPLING WITH LOCK RING AND FEMALE BSP THREAD

SIZE	CODE
1-1/2"(DN40)	GFL-150-AL/SS
2"(DN50)	GFL-200-AL/SS
2-1/2"(DN65)	GFL-250-AL/SS
3"(DN80)	GFL-300-AL/SS
4"(DN100)	GFL-400-AL/SS

**STYLE**



GULLEMIN COUPLING WITHOUT LOCK RING AND MALE BSP THREAD

SIZE	CODE
1-1/2"(DN40)	GHL-150-AL/SS
2"(DN50)	GHL-200-AL/SS
2-1/2"(DN65)	GHL-250-AL/SS
3"(DN80)	GHL-300-AL/SS
4"(DN100)	GHL-400-AL/SS

**STYLE**



GULLEMIN COUPLING BLANK CAP WITH LOCK RING AND CHAIN

SIZE	CODE
1-1/2"(DN40)	GBC-150-AL/SS
2"(DN50)	GBC-200-AL/SS
2-1/2"(DN65)	GBC-250-AL/SS
3"(DN80)	GBC-300-AL/SS
4"(DN100)	GBC-400-AL/SS