


欧标H型钢 EXTRA WIDE FLANGE BEAMS HL AND HLZ

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993




尺寸和截面特性 Dimensions and Sectional Properties
 尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.
 EN 10025-3 S275N/NL, S355N/NL etc.
 EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
HL920*344	344.0	927	418	19.3	32.0	19.0	437.2
HL920*368	368.0	931	419	20.3	34.3	19.0	465.6
HL920*390	390.0	936	420	21.3	36.6	19.0	494.3
HL920*420	420.0	943	422	22.5	39.9	19.0	534.1
HL920*449	449.0	948	423	24.0	42.7	19.0	571.4
HL902*491	491.0	957	422	25.9	47.0	19.0	623.3
HL920*537	537.0	965	425	28.4	51.1	19.0	682.5
HL920*588	588.0	975	427	31.0	55.9	19.0	748.1
HL920*656	656.0	987	431	34.5	62.0	19.0	835.3
HL920*725	725.0	999	434	38.1	68.1	19.0	922.9
HL920*787	787.0	1011	437	40.9	73.9	19.0	1002.0
HL920*970	970.0	1043	446	50.0	89.9	19.0	1237.0
HL920*1077	1077.0	1061	451	55.0	99.1	19.0	1372.0
HL920*1194	1194.0	1081	457	60.5	109.0	19.0	1522.0
HL920*1269	1269.0	1093	461	64.0	115.1	19.0	1617.0
HL920*1377	1377.0	1093	473	76.7	115.1	19.0	1754.0
HL1000AA	296.0	982	400	16.5	27.1	30.0	377.6
HL1000A	321.0	990	400	16.5	31.0	30.0	408.8
HL1000B	371.0	1000	400	19.0	36.1	30.0	472.8
HL1000M	412.0	1008	402	21.1	40.0	30.0	525.1

欧标H型钢 EXTRA WIDE FLANGE BEAMS HL AND HLZ

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993



尺寸和截面特性 Dimensions and Sectional Properties
 尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.
 EN 10025-3 S275N/NL, S355N/NL etc.
 EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
HL1000*443	443.0	1012	402	23.6	41.9	30.0	563.7
HL1000*483	483.0	1020	404	25.4	46.0	30.0	615.1
HL1000*539	539.0	1030	407	28.4	51.1	30.0	687.2
HL1000*554	554.0	1032	408	29.5	52.0	30.0	705.8
HL1000*591	591.0	1040	409	31.0	55.9	30.0	752.7
HL1000*642	642.0	1048	412	34.0	60.0	30.0	817.6
HL1000*748	748.0	1068	417	39.0	70.0	30.0	953.4
HL1000*883	883.0	1092	424	45.5	82.0	30.0	1125.0
HL1000*976	976.0	1108	428	50.0	89.9	30.0	1243.0
HL1100A	343.0	1090	400	18.0	31.0	20.0	436.5
HL1100B	390.0	1100	400	20.0	36.0	20.0	497.0
HL1100M	433.0	1108	402	22.0	40.0	20.0	551.2
HL1100R	499.0	1118	405	26.0	45.0	20.0	635.2
HL1100*548	548.0	1128	407	28.0	50.0	20.0	698.3
HL1100*607	607.0	1138	410	31.0	55.0	20.0	773.1
HLZ1100A	393.0	1075.4	458	20.0	31.0	35.0	500.8
HLZ1100B	408.0	1079.4	458	20.0	33.0	35.0	519.1
HLZ1100C	430.0	1083.4	459	21.0	35.0	35.0	548.3
HLZ1100D	453.0	1087.4	460	22.0	37.0	35.0	577.5