


欧标H型钢 WIDE FLANGE BEARING PILES HP

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993




尺寸和截面特性 Dimensions and Sectional Properties

尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.
EN 10025-3 S275N/NL, S355N/NL etc.
EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
HP200*43	42.5	200.0	205.0	9.0	9.0	10.0	54.1
HP200*53	53.5	204.0	207.0	11.3	11.3	10.0	68.4
HP220*57	57.2	210.0	224.5	11.0	11.0	18.0	72.9
HP260*75	75.0	249.0	265.0	12.0	12.0	24.0	95.5
HP260*87	87.3	253.0	267.0	14.0	14.0	24.0	111.0
HP305*79	78.9	299.3	306.4	11.0	11.1	15.2	100.5
HP305*88	88.5	301.7	307.8	12.4	12.3	15.2	112.1
HP305*95	94.9	303.7	308.7	13.3	13.3	15.2	121.0
HP305*110	110.0	307.9	310.7	15.3	15.4	15.2	140.1
HP305*126	126.0	312.3	312.9	17.5	17.6	15.2	160.6
HP305*149	149.0	318.5	316.0	20.6	20.7	15.2	189.9
HP305*180	180.0	326.7	319.7	24.8	24.8	15.2	229.3
HP305*186	186.0	328.3	320.9	25.5	25.6	15.2	236.9
HP305*223	223.0	337.9	325.7	30.3	30.4	15.2	284.0
HP320*88	88.5	303.0	304.0	12.0	12.0	27.0	112.7
HP320*103	103.0	307.0	306.0	14.0	14.0	27.0	113.0

欧标H型钢 WIDE FLANGE BEARING PILES HP

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993



尺寸和截面特性 Dimensions and Sectional Properties
 尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.
 EN 10025-3 S275N/NL, S355N/NL etc.
 EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
HP320*117	117.0	311.0	308.0	16.0	16.0	27.0	149.5
HP320*147	147.0	319.0	312.0	20.0	20.0	27.0	186.9
HP320*184	184.0	329.0	317.0	25.0	25.0	27.0	234.5
HP360*109	109.0	346.4	371.0	12.8	12.9	15.2	138.7
HP360*133	133.0	352.0	373.8	15.6	15.7	15.2	169.4
HP360*152	152.0	356.4	376.0	17.8	17.9	15.2	193.7
HP360*174	174.0	361.4	378.5	20.3	20.4	15.2	221.5
HP360*180	180.0	362.9	378.8	21.1	21.1	15.2	229.5
HP400*122	122.0	348.0	390.0	14.0	14.0	15.0	155.9
HP400*140	140.0	352.0	392.0	16.0	16.0	15.0	178.6
HP400*158	158.0	356.0	394.0	18.0	18.0	15.0	201.4
HP400*176	176.0	360.0	396.0	20.0	20.0	15.0	224.3
HP400*194	194.0	364.0	398.0	22.0	22.0	15.0	247.5
HP400*213	213.0	368.0	400.0	24.0	24.0	15.0	270.7
HP400*231	231.0	372.0	402.0	26.0	26.0	15.0	294.2