


欧标工字钢 PARALLEL FLANGE I SECTIONS IPE

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993




尺寸和截面特性 Dimensions and Sectional Properties
 尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.
 EN 10025-3 S275N/NL, S355N/NL etc.
 EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
IPEAA80	4.9	78.0	46.0	3.2	4.2	5.0	6.3
IPEA80	5.0	78.0	46.0	3.3	4.2	5.0	6.4
IPE80	6.0	80.0	46.0	3.8	5.2	5.0	7.6
IPEAA100	6.7	97.6	55.0	3.6	4.5	7.0	8.6
IPEA100	6.9	98.0	55.0	3.6	4.7	7.0	8.8
IPE100	8.1	100.0	55.0	4.1	5.7	7.0	10.3
IPEAA120	8.4	117.0	64.0	3.8	4.8	7.0	10.7
IPEA120	8.7	117.6	64.0	3.8	5.1	7.0	11.0
IPE120	10.4	120.0	64.0	4.4	6.3	7.0	13.2
IPEAA140	10.1	136.6	73.0	3.8	5.2	7.0	12.8
IPEA140	10.5	137.4	73.0	3.8	5.6	7.0	13.4
IPE140	12.9	140.0	73.0	4.7	6.9	7.0	16.4
IPEAA160	12.3	156.4	82.0	4.0	5.6	9.0	15.7
IPEA160	12.7	157.0	82.0	4.0	5.9	9.0	16.2
IPE160	15.8	160.0	82.0	5.0	7.4	9.0	20.1
IPEAA180	14.9	176.4	91.0	4.3	6.2	9.0	19.0
IPEA180	15.4	177.0	91.0	4.3	6.5	9.0	19.6
IPE180	18.8	180.0	91.0	5.3	8.0	9.0	23.9
IPEO180+	21.3	182.0	92.0	6.0	9.0	9.0	27.1
IPEAA200	18.0	196.4	100.0	4.5	6.7	12.0	22.9
IPEA200	18.4	197.0	100.0	4.5	7.0	12.0	23.5
IPE200	22.4	200.0	100.0	5.6	8.5	12.0	28.5
IPEO200	25.1	202.0	102.0	6.2	9.5	12.0	32.0
IPEAA220	21.2	216.4	110.0	4.7	7.4	12.0	27.0
IPEA220	22.2	217.0	110.0	5.0	7.7	12.0	28.3

欧标工字钢 PARALLEL FLANGE I SECTIONS IPE

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993




尺寸和截面特性 Dimensions and Sectional Properties
 尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.
 EN 10025-3 S275N/NL, S355N/NL etc.
 EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
IPE220	26.2	220.0	110.0	5.9	9.2	12.0	33.4
IPEO220	29.4	222.0	112.0	6.6	10.2	12.0	37.4
IPEAA240	24.9	236.4	120.0	4.8	8.0	15.0	31.7
IPEA240	26.2	237.0	120.0	5.2	8.3	15.0	33.3
IPE240	30.7	240.0	120.0	6.2	9.8	15.0	39.1
IPEO240	34.3	242.0	122.0	7.0	10.8	15.0	43.7
IPEA270	30.7	267.0	135.0	5.5	8.7	15.0	39.2
IPE270	36.1	270.0	135.0	6.6	10.2	15.0	45.9
IPEO270	42.3	274.0	136.0	7.5	12.2	15.0	53.8
IPEA300	36.5	297.0	150.0	6.1	9.2	15.0	46.5
IPE300	42.2	300.0	150.0	7.1	10.7	15.0	53.8
IPEO300	49.3	304.0	152.0	8.0	12.7	15.0	62.8
IPEA330	43.0	327.0	160.0	6.5	10.0	18.0	54.7
IPE330	49.1	330.0	160.0	7.5	11.5	18.0	62.6
IPEO330	57.0	334.0	162.0	8.5	13.5	18.0	72.6
IPEA360	50.2	357.6	170.0	6.6	11.5	18.0	64.0
IPE360	57.1	360.0	170.0	8.0	12.7	18.0	72.7
IPEO360	66.0	364.0	172.0	9.2	14.7	18.0	84.1
IPEA400	57.4	397.0	180.0	7.0	12.0	21.0	73.1
IPE400	66.3	400.0	180.0	8.6	13.5	21.0	84.5
IPEO400	75.7	404.0	182.0	9.7	15.5	21.0	96.4
IPEV400	84.0	408.0	182.0	10.6	17.5	21.0	107.0
IPEA450	67.2	447.0	190.0	7.6	13.1	21.0	85.6
IPE450	77.6	450.0	190.0	9.4	14.6	21.0	98.8
IPEO450	92.4	456.0	192.0	11.0	17.6	21.0	117.7

欧标工字钢 PARALLEL FLANGE I SECTIONS IPE

尺寸标准/DIMENSIONS: BS EN10365-2017 公差标准/TOLERANCES: EN10034:1993



尺寸和截面特性 Dimensions and Sectional Properties

尺寸材质Material EN 10025-2 S235JR, S275JR, S355JR etc.

EN 10025-3 S275N/NL, S355N/NL etc.

EN 10025-4 S275M/ML, S355M/ML etc.

型号 Designation	米重 (kg/m) Unit Weight (kg/m)	高度 H (mm)	腿宽 B (mm)	腹板 厚度t1 (mm)	翼缘 厚度t2 (mm)	圆角 半径r (mm)	截面面积 A (cm ²)
IPEV450	104.0	460.0	194.0	12.4	19.6	21.0	132.0
IPEA500	79.4	497.0	200.0	8.4	14.5	21.0	101.1
IPE500	90.7	500.0	200.0	10.2	16.0	21.0	115.5
IPEO500	107.0	506.0	202.0	12.0	19.0	21.0	136.7
IPEV500	129.0	514.0	204.0	14.2	23.0	21.0	164.1
IPEA550	92.1	547.0	210.0	9.0	15.7	24.0	117.3
IPE550	106.0	550.0	210.0	11.1	17.2	24.0	134.4
IPEO550	123.0	556.0	212.0	12.7	20.2	24.0	156.1
IPEV550	159.0	566.0	216.0	17.1	25.2	24.0	202.0
IPEA600	108.0	597.0	220.0	9.8	17.5	24.0	137.0
IPE600	122.0	600.0	220.0	12.0	19.0	24.0	156.0
IPEO600	154.0	610.0	224.0	15.0	24.0	24.0	196.8
IPEV600	184.0	618.0	228.0	18.0	28.0	24.0	233.8
IPE750*134	134.0	750.0	264.0	12.0	15.5	24.0	170.6
IPE750*137	137.0	753.0	263.0	11.5	17.0	17.0	174.6
IPE750*147	147.0	753.0	265.0	13.2	17.0	17.0	187.5
IPE750*161	161.0	758.0	266.0	13.8	19.3	17.0	204.4
IPE750*173	173.0	762.0	267.0	14.4	21.6	17.0	221.3
IPE750*185	185.0	766.0	267.0	14.9	23.6	17.0	227.8
IPE750*196	196.0	770.0	268.0	15.6	25.4	17.0	250.8
IPE750*210	210.0	775.0	268.0	16.0	28.0	17.0	267.8
IPE750*222	222.0	778.0	269.0	17.0	29.5	17.0	283.4